

# Murray

## TEF2+4C Kawneer Style Pivot



**SKU:** TEF2+4KEP

**Made to order:** This item may have a 3-5 day processing time

Eligible for FREE Shipping

We take these factory original Kawneer style pivots and machine them in our factory to close tolerance. This 2+4 wire Power Transfer Pivot is aluminum base material with our proprietary Teflon jacketed wires. This pivot can be used for electric latch retraction panic exit devices. The two heavy 20 awg wires will handle any electric latch retraction panic exit device on the market today.

If you are unsure as to which hand you need and you have an existing Kawneer mechanical pivot on the door, you can remove the pivot and look at the back. There should be a stamped or cast LH or RH on the back. If you aren't replacing a pivot and need one for a new job and are unsure of the hand, please contact our tech support person by calling 800.500.1449.

We stock a limited quantity of Kawneer Style Pivots at our facility and these pivots are made to order. Small orders have a 3-5 day processing time and larger orders may take an additional 3-5 days for processing, depending on the quantity ordered. If you have any questions please contact customer service at 800-500-1449

### **Low Voltage Rating:**

**TEF2+4C**, 16 amp surge, 15 sec., 5 amp continuous., (20 awg pair) , 2 pair, 28 awg, .10 amp (100 mA) 12 or 24 Volt AC/DC (up to 48V AC/DC)

**TEF10C**, all wires 28 awg, 1 amp-one pair, .10 amp (100 mA) remaining pairs, 12 or 24 Volt AC/DC (up to 48V AC/DC)

**TEF2+10C**, 16 amp surge, 15 sec., 5 amp continuous, (20 awg pair) , 5 pair .10 amp (100 mA) 28 awg wires 12 or 24 Volt AC/DC (up to 48V AC/DC)